

ORBEA



ORCA OMX-D.

BESCHIKBAAR IN DEZE KLEUREN:



ZWART (MAT)



JADEGROEN MET.
(GLANZEND) / ZWART (MAT)



GRIJS - BRIGHT RED (MAT)

SPECIFICATIES AND OPTIES

FIETSFRAME	Orbea Orca carbon OMX Disc, monocoque construction, HS 1,5", BB 386mm, powermeter compatible, Rear Thru Axle 12x142mm, thread M12x2 P1, internal cable routing, EC/DC compatible, OMX specific seat tube.
VORK	steerer, tapered 1-1/8" - 1,5", carbon dropouts, Thru axle 12x100mm, thread M12x2 P1
BALHOOFDLAGER PERB	Acros Alloy 1-1/2" Internal Cable Routing
STUURPEN	Orbea ICR -8°
ZADELPEN	Orbea Orca OMX SB0-25mm
COMPONENTE EN BLANCO (WEB)	
VÓOR NAAF	OC Thru Axle 12x100mm M12x2 P1
NAAF	OC Thru Axle 12x142mm M12x2 P1

GEOMETRIE

MAAT	47	49	51	53	55	57	60
1 - SEAT_TUBE	440	460	480	500	520	540	570
2 - TOP_TUBE	510,45	523,24	535,84	548,51	560,43	576,13	589,97
3 - HEAD_TUBE	105,6	113,2	129,6	147,9	168	186,2	213,3
4 - CHAIN_STAY				408			
5 - BB_HEIGHT	264	264	264	266	266	266	266
6 - BB_DROP	72	72	72	70	70	70	70
7 - WHEELBASE	971,9	976	980	981,17	991,39	1001,86	1015,7
8 - HEAD_ANGLE	71°	71,5°	72,20°	72,80°	73,00°	73,20°	73,20°
9 - SEAT_ANGLE	74,5°	74°	73,7°	73,5°	73,5°	73,2°	73,2°
10 - STANDOVER	726,48	739,84	758,48	778,84	799,12	817,55	845,06
11 - REACH	370,08	375,56	380	385	391,02	398	404
12 - STACK	506,06	515	533	552	571,92	590	616
13 - FORK_LENGTH				370			
14 - OFFSET	48	48	48	43	43	43	43

ERGONOMIE

MAAT	CRANK	STEM	HANDLEBAR
47	170	90	400
49	170	100	400
51	170	100	420
53	170	110	420
55	172	110	420
57	172	110	440
60	175	120	440

* De maat van het fietsstuur is centre-centre

